



ATC800



ATC1500



ATC2500



ATC2500E



ATC4500E



ATC4800E



ATC6500E



ATC6500E2

Rated output	700W	1000W	2000W	2000W	2500W	2800W	5000W	5000W
Max output	800W	1200W	2300W	2300W	2800W	3100W	5500W	5500W
Frequcney	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz
Phase	Single	Single	Single	Single	Single	Single	Single	Single
Power factor	1	1	1	1	1	1	1	1
Engine	2.8HP,Single cylinder, 2-Stroke,OHV,Air cooled	2.8HP,Single cylinder, 4-Stroke,OHV,Air cooled	5.5HP,Single cylinder, 4-Stroke,OHV,Air cooled	5.5HP,Single cylinder, 4-Stroke,OHV,Air cooled	6.5HP,Single cylinder, 4-Stroke,OHV,Air cooled	9.0HP,Single cylinder, 4-Stroke,OHV,Air cooled	13.0HP,Single cylinder, 4-Stroke,OHV,Air cooled	13.0HP,Single cylinder, 4-Stroke,OHV,Air cooled
Fuel	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline
Fuel tank capacity	4.2L	6L	15L	15L	15L	25L	25L	25L
Start system	Recoil	Recoil	Recoil	Recoil+Electric	Recoil+Electric	Recoil+Electric	Recoil+Electric	Recoil+Electric
Noise Level@7m	60dB (A)	60dB (A)	68dB (A)	68dB (A)	68dB (A)	68dB (A)	72dB (A)	72dB (A)
Dimension	375x330x325 mm	460x370x390 mm	605x445x465 mm	605x465x465 mm	605x465x465 mm	700x535x570 mm	700x535x570 mm	815x570x575 mm

- E: Key Start + Battery
- E2: Key Start + Battery + Wheel + Handle