

DEMIN

DEMIN



NO.	SPECIFICATIONS	DM 20/E	DM 30/E	DM 40/E
1	water inlet/outlet diameter mm(in)	50(2)	80(3)	100(4)
2	rated flow m ³ /h	22	30	40
3	max hydraulic head lift m	28	28	28
4	Max suction head lift m	8	8	8
5	displacement cc	211	305	418
6	self priming s/m	80s/4m	120s/4m	180s/4m
7	rated output kva	2.8	4.0	6.3
8	rotate speed rpm	3600	3600	3600
9	engine model	HH170F/HH170FE	HH178FA/HH178FAE	HH186FA/HH186FAE
10	starting mode	recoil/electric	recoil/electric	recoil/electric
11	start motor v;kw	12 V 0.8 kW	12 V 0.8 kW	12 V 0.8 kW
12	battery v;ah	12 V 24Ah	12 V 24Ah	12 V 24 Ah
13	fuel tank capacity L	2.5	3.5	5.5
14	outline dimensions mm(in)	535X455X535	565X475X580	655X515X620
15	net weight kg	35/38.5	49/52	63/69
16	gross weight kg	37/40.5	51.5/54.5	66/72



Sole Agent & Distributor

Deira, Dubai-UAE Tel:00971-4-2217124 Fax:00971-4-223-4493
Email:inquiry@alawigroup.ae Website:www.alawigroup.ae