












EG 13000



-  Eagle Powerful 622CC single-cylinder engine
-  Automatic Voltage Regulation (AVR)
-  Low oil level automatic protection
-  Current over current protection
-  Large fuel tank capacity 48L
-  Long continuous running (7 hours)
-  Extra-large oil tank for long working time
-  Frame type safety support
-  With wheels and handle



Specifications

Model	EG 13000
Engine model	LC196FD
Engine type	Single cylinder, 4-stroke, forced cooling, OHV, forced lubrication
Power output	13.3 kW / 3600 rpm
Bore x Stroke	96 mm x 86 mm
Displacement	622 ml
Oil tank capacity	1.6 L
Fuel tank capacity	48 L
Fuel consumption	≤ 374 g/kW.h
Continuing time	10 hours
Rated frequency	50 Hz
Rated voltage	240 V
Max. Current	41 A
Voltage regulator system	Automatic Voltage Regulation (AVR)
Output power	6.5 kW
Power factor (cos θ)	1.0
Charging voltage	12 V (DC)
Charging current	8.3 A (DC)
Starting system	Recoil and Electric start
Ignition system	Transistorised magneto
Noise (@ 7m)	≤ 76 dB (A)
Dimensions	800 x 620 x 650 mm
Net weight	143 kg

