



EG 2500



- ✈ Eagle commercial grade OHV engine
- ✈ Automatic Voltage Regulation (AVR)
- ✈ Low oil level automatic protection
- ✈ Current over current protection
- ✈ Large fuel tank capacity 18L
- ✈ Long continuous running (15 hours)
- ✈ Frame type safety support
- ✈ With or without wheels and handle
- ✈ Start, recoil or E-start



Specifications

Model	EG 2500 A/DA
Engine model	G200F/G200FD
Engine type	Single cylinder, 4-stroke, forced cooling, OHV
Power output	4.1 kW / 3600 rpm
Bore x Stroke	68 mm x 54 mm
Displacement	196 ml
Compression ratio	8.5:1
Oil tank capacity	0.6 L
Fuel tank capacity	18 L
Fuel consumption	≤ 395 g/kW.h
Continuing time	15 hours
Rated frequency	50 Hz
Rated voltage	240 V
Voltage regulator system	Automatic Voltage Regulation (AVR)
Output power	2.2 kW
Power factor (cos θ)	1.0
Charging voltage	12 V (DC)
Charging current	8.3 A (DC)
Starting system	Recoil start/Electric start
Ignition system	Transistorised magneto
Noise (@ 7m)	≤ 75 dB (A)
Dimensions	590 x 430 x 480 mm
Net weight	43/45 kg

