












## EG 6500



-  Eagle commercial grade OHV engine
-  Automatic Voltage Regulation (AVR)
-  Low oil level automatic protection
-  Current over current protection
-  Large fuel tank capacity 25L
-  Long continuous running (9 hours)
-  Frame type safety support
-  With or without wheels and handle
-  Start, recoil or E-start



## Specifications

Model	EG 6500 A/DA
Engine model	G390A/G390FD
Engine type	Single cylinder, 4-stroke, forced cooling, OHV
Power output	8.2 kW / 3600 rpm
Bore x Stroke	88 mm x 64 mm
Displacement	389 ml
Compression ratio	8:1
Oil tank capacity	1.1 L
Fuel tank capacity	25 L
Fuel consumption	≤ 374 g/kW.h
Continuing time	9 hours
Rated frequency	50 Hz
Rated voltage	240 V
Voltage regulator system	Automatic Voltage Regulation (AVR)
Output power	5.5 kW
Power factor (cos θ)	1.0
Charging voltage	12 V (DC)
Charging current	8.3 A (DC)
Starting system	Recoil start/Electric start
Ignition system	Transistorised magneto
Noise (@ 7m)	≤ 76 dB (A)
Dimensions	675 x 540 x 540 mm
Net weight	77/79 kg

