



EURARC 422 230V/400V



ROBIN MACHINERY & EQUIPMENT
SOURCE OF TRUST



Overview

EURARC 422 230V/400V

cod. 817017

MMA stick electrode welding machine in alternating current (AC). Stepless regulation of welding current. With thermostatic protection. The model has double secondary voltage for use also with basic and rutile electrodes.



MMA 2AC



1 PH 230V



2 PH 400V



FAN COOLED



CE MARKING



EAC CERTIFICATION

Technical data



CODE 817017



MAINS VOLTAGE 230 - 1 ph V50/60Hz



MAINS VOLTAGE 400 - 2 ph V50/60Hz



CURRENT RANGE 70 - 350 AC A



MAX CURRENT 215 - 35% AC A EN60974-1



CURRENT AT 60% 170 AC A EN60974-1



MAX NO LOAD VOLTAGE IN AC 52 - 73 AC V



ABSORBED POWER AT 60% - MAX 4,5 - 13 kW



POWER FACTOR 0,4 cosphi



D. USABLE ELECTRODES IN AC 2 - 6 mm



PROTECTION DEGREE IP22



DIMENSIONS 83 - 45,5 - 58 cm(L,W,H)



WEIGHT 61 kg



EAN CODE 800489784789 4



PIECES/PALLET 6 pz/pallet



PIECES/PALLET - B 3 pz/pallet - B