



EURARC 522 230V/400V



ROBIN MACHINERY & EQUIPMENT
SOURCE OF TRUST



Overview

EURARC 522 230V/400V

cod. 817018

MMA stick electrode welding machine in alternating current (AC). Stepless regulation of welding current. With thermostatic protection. The model has double secondary voltage for use also with basic and rutile electrodes.



MMA 2AC



1 PH 230V



2 PH 400V



FAN COOLED



CE MARKING



EAC CERTIFICATION

Technical data



CODE 817018



MAINS VOLTAGE 230 - 1 ph V50/60Hz



MAINS VOLTAGE 400 - 2 ph V50/60Hz



CURRENT RANGE 40 - 400 AC A



MAX CURRENT 350 - 35 % AC A EN60974-1



CURRENT AT 60% 265 AC A EN60974-1



MAX NO LOAD VOLTAGE IN AC 52 - 71 AC V



ABSORBED POWER AT 60% - MAX 11 - 15 kW



POWER FACTOR 0,7 cosphi



D. USABLE ELECTRODES IN AC 1,6 - 6 mm



PROTECTION DEGREE IP22



DIMENSIONS 95 - 49 - 68 cm(L,W,H)



WEIGHT 81 kg



EAN CODE 800489785092 4



PIECES/PALLET 6 pz/pallet



PIECES/PALLET - B 3 pz/pallet - B