Clear Water Pump














■ Performance Curve





■ Specifications

| | Model | SEV-50X | SEV-80X |
|-----------------------|---------------------------|--|-------------------------------------|
| PUMP | Connection Dia | 50 mm (2") | 80 mm (3") |
| | Connection Thread | Outer Pipe Thread BSP | |
| | Total Head | 27 m (90 ft) | |
| | Delivery Volume | 620 L/min (163 USG/min) | 1050 L/min (277 USG/min) |
| | Max. Suction Head | 8 m (26 ft) | |
| ENGINE | Туре | Forced Air-cooled 4-stroke Gasoline Engine | |
| | Model | Koshin K180 | |
| | Exhaust Volume | 179 cc | |
| | Rated Output | 3.1 kW (4.2 PS) / 3600 rpm | |
| | Fuel | Automotive Unleaded Gasoline | |
| | Fuel Tank Capacity | 3.6 L (0.95 USG) | |
| | Continuous Operating Time | Approx. 2.6 hrs | Approx. 2.4 hrs |
| | Starting Method | Recoil Starter | |
| Standard Accessories | | 1 Strainer, 3 Hose Bands, | 2 Hose Couplings, 1 Engine Tool Set |
| Gross Weight | | 27.2 kg (59.9 lbs) | 30.7 kg (67.6 lbs) |
| Dimensions L×W×H (mm) | | 504 × 400 × 411 | 543 × 425 × 458 |
| Packing Unit | | 1 | |

^{*}For the purpose of improvement, specifications are subject to changes without notice.