

Loncin 隆鑫

LC 13000



- With Loncin strong high performance engine
- AVR, auto voltage regulator
- Low oil sensor protection
- Cradle, overall protection, easy move and storage
- With wheels and handle
- Recoil and E-start
- Thermal overload cut out protection



ROBIN MACHINERY & EQUIPMENT
SOURCE OF TRUST

Specifications

Model	LC13000 DA
Engine model	LC196FD
Engine type	Single cylinder, 4-stroke, forced cooling, OHV, forced lubrication
Power output	13.3 kW / 3600 rpm
Bore x Stroke	96 mm x 86 mm
Displacement	622 ml
Oil tank capacity	1.6 L
Fuel tank capacity	48 L
Fuel consumption	≤ 374 g/kW.h
Continuing time	10 hours
Rated frequency	50 Hz
Rated voltage	240 V
Max. Current	41 A
Voltage regulator system	Automatic Voltage Regulation (AVR)
Output power	6.5 kW
Power factor (cos θ)	1.0
Charging voltage	12 V (DC)
Charging current	8.3 A (DC)
Starting system	Recoil and Electric start
DC Voltage/current	12 V / 8.3 A
Ignition system	Transistorised magneto
Noise (@ 7m)	≤ 76 dB (A)
Dimensions	800 x 620 x 650 mm
Net weight	143 kg

