

# **LONCIN** 隆鑫

LC 2500



- With Loncin strong commercial engine
- AVR, auto voltage regulator
- Low oil sensor protection
- Cradle, overall protection, easy move and storage
- With or without wheels and handle
- Start, recoil or E-start



**ROBIN MACHINERY & EQUIPMENT**  
SOURCE OF TRUST

## Specifications

Model	LC2500 A/DA
Engine model	G200F/G200FD
Engine type	Single cylinder, 4-stroke, forced cooling, OHV
Power output	4.1 kW / 3600 rpm
Bore x Stroke	68 mm x 54 mm
Displacement	196 ml
Compression ratio	8.5:1
Oil tank capacity	0.6 L
Fuel tank capacity	18 L
Fuel consumption	≤ 395 g/kW.h
Continuing time	15 hours
Rated frequency	50 Hz
Rated voltage	240 V
Voltage regulator system	Automatic Voltage Regulation (AVR)
Output power	2.2 kW
Power factor (cos θ)	1.0
Charging voltage	12 V (DC)
Charging current	8.3 A (DC)
Starting system	Recoil start/Electric start
Ignition system	Transistorised magneto
Noise (@ 7m)	≤ 75 dB (A)
Dimensions	590 x 430 x 480 mm
Net weight	43/45 kg

