

LONCIN 隆鑫

LC 3500



- With Loncin strong commercial engine
- AVR, auto voltage regulator
- Low oil sensor protection
- Cradle, overall protection, easy move and storage
- With or without wheels and handle
- Start, recoil or E-start



ROBIN MACHINERY & EQUIPMENT
SOURCE OF TRUST

Specifications

Model	LC3500 A/DA
Engine model	G210FA/G210FAD
Engine type	Single cylinder, 4-stroke, forced cooling, OHV
Power output	4.4 kW / 3600 rpm
Bore x Stroke	70 mm x 55 mm
Displacement	212 ml
Compression ratio	8.5:1
Oil tank capacity	0.6 L
Fuel tank capacity	18 L
Fuel consumption	≤ 395 g/kW.h
Continuing time	11 hours
Rated frequency	50 Hz
Rated voltage	240 V
Voltage regulator system	Automatic Voltage Regulation (AVR)
Output power	3.1 kW
Power factor (cos θ)	1.0
Charging voltage	12 V (DC)
Charging current	8.3 A (DC)
Starting system	Recoil start/Electric start
Ignition system	Transistorised magneto
Noise (@ 7m)	≤ 7.6 dB (A)
Dimensions	675 x 540 x 540 mm
Net weight	68/70 kg

