

2014-2015 MARUYAMA PRODUCT CATALOGUE ASIA





Chainsaws

Chainsaws







REAR HANDLE CER Eco engine



35.0cc 4.2kg

16 inch Standard

Bar Length

Model MCV3501 Displacement (ml) 34.9 Fuel tank (L) 0.34 Handle Rear Guide bar Sprocket nose, 16 91PX Saw chain Oil pump Auto Brake system Normal Recoil starter Reverse 2

Dry weight (kg)

4.2





Our patented "E JUST" chain tensionon the front handle for quick chain

Chainsaw Features



Reverse Start 2 Reverse Start 2 system incorperates the best features of an electric starter for fast and easy



Pre-Vent System Debri and saw dust are dispersed leaving only clean air running through the carburetor.



Hybrid Anti-Vibration Anti-vibration spring and rubber dampers ensures a smoother cut each and













Mist Blower



he large turbo fan allows or maximum air flow. Ip to 24 meters spraying



Fitted with soft waterproof padding for maximum comfort during operation.



Comes in 13L, 20L and 30L Difference sizes for different situations.

Mist Blower





TK65





64.7cc 20 L



20 m3/min

11.7 kg


Model MD180DX-20 Engine model TK65 Displacement (ml) 64.7 Fuel tank (L) 2.0 Chemical tank (L) 20 Air volume (m3 min) 20.0 Discharge volume (Lmin) 3.8 (adjustable) Throttle Trigger 11.5 Dry weight (kg)

Mist Attachments




















PUMP TYPE	TR	TRIPLEX UNIFLOW PUMP				
DIMENSIONS (LXWXH)	mm	342.5X200X254.8				
WEIGHT(DRY)	kg	6.5				
MAXIMUM FLOW RATE	L/min	40				
MAXIMUM PRESSURE	MPa	3.5				
PUMP ROTATING SPEED	min-1	1250				
REQUIRED POWER	kW	3.0				
V-PULLEY	mm	φ191-AX2 (7.5in)				



ROBIN MACHINERY & EQUIPMENT







Complete with engine

MSD41 Compact Power Sprayer






- Compact and light weight, pump is directly connected to the engine.
- •The engine can be set at(3. 6PS)or more if needed.
- •With a high pressure output of 4. OMPa, the MSD41 is not only ideal for pest control but also cleaning
- Easily switch between pressure ranges with pressure dial.
- •With Maruyama's high efficeincy piston pump, high water absorbtion is achieved even at low rpm.

Specifications

Dimensions (LxWxH) mm	195x255x210					
Weight kg	5.6					
Revolutions per minute	3600					
Max Pressure MPa	4.0					
Suction Volume L/min	30					
Required power PS(kW)	3.6 (2.7) or more					
Spray Cock	G3/8					
Accessories	flange, bolt kit, intake hose 3m addition hose 3m, strainer					
Crank shaft diameter ϕ mm	20					
Crank shaft length mm	45					
Key Size mm	5					



Engine Set







TSW41



4.0hp

Max Pressure 4.0Mpa



No tank

Spray hose

26 kg

(a 10m





Maruyama Engine Set Sprayers incorperates the reliability and power of our pumps to give you a machine out perform and outlast anything you have ever used before.

Our pumps provide smooth constant pressure that can be adjusted to your need.

Designed for large area spraying, such as crop fields and paddy fields, you can take your machine where ever you need to go.

The robust frames and wheels provides easy manuverability, just strap it up at the back of you truck and take it with you to your next job.



Model	Eng	jine	Power	Suction	Max	Spray Hose				Transporting	Chemical Tank	Dry weigh		
		Sprayer	Volume Pressure											
				(L/min)	(MPa)	(m)	Ф8.5	Ф10	Ф11.5	Ф13	Self-winding	Self-Propelled		(kg)
											System	System		
TSW41	4.0ps	EX170	MSD41	30	4.0	10	2	•	-	-	-	-	-	26.0



