



TECHNOLOGY 238 CE/MPGE 230V ACX+ALU C.C.



ROBIN MACHINERY & EQUIPMENT
SOURCE OF TRUST



EMF SAFE	WITH CARRY CASE ACCESSORIES	RECOMMENDED FOR
MULTI PROTECTIONS FOR GENERATOR	Cellulosic	Aluminium

Overview

TECHNOLOGY 238 CE/MPGE 230V ACX+ALU C.C.

cod. 816213

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking. Designed for welding cellulosic electrodes and coated electrodes such as aluminium, rutile, basic, stainless steel and cast iron electrodes with diameter up to 4 mm. It can be connected to motorgenerators. Characteristics: compact and light * high welding current stability in spite of mains voltage fluctuations * arc force, hot start and anti-stick devices * thermostatic, overvoltage, undervoltage, overcurrent protections * multiprotectons for motorgenerators. Complete with MMA welding accessories and aluminium carry case.



MMA TIG DC SCRATCH



1 PH 230V



FAN COOLED



CE MARKING



EAC CERTIFICATION



TÜV CERTIFICATION

Technical data



CODE 816213



MAINS VOLTAGE 230 - 1 ph V50/60Hz



CURRENT RANGE 5 - 180 DC A



MAX CURRENT 180 - 35 % DC A EN60974-1



CURRENT AT 60% 140 DC A EN60974-1



MAX NO LOAD VOLTAGE IN AC 102 DC V



ABSORBED CURRENT AT 60% - MAX 27 - 36 A



ABSORBED POWER AT 60% - MAX 4,3 - 6 kW



MOTORGENERATOR MINIMUM POWER 9 kW



EFFICIENCY 84 n%



POWER FACTOR 0,7 cosphi



D. USABLE ELECTRODES IN DC 1,6 - 4 mm



TECHNOLOGY 238 CE/MPGE 230V ACX+ALU C.C.



PROTECTION DEGREE IP23



DIMENSIONS 35,5 - 46,5 - 18,5 cm(L,W,H)



WEIGHT 10,1 kg



EAN CODE 800489782873 2



PIECES/PALLET 30 pz/pallet

Included Accessories

CABLE 25 MMQ 2 M DINSE 25 - 124465

CABLE 25 MMQ 3 M DINSE DX 25 - 124466



DALLAS 300 ELECTRODE HOLDER 300A - 712260



TOLEDO 300 WORK CLAMP - 712231

